

FORM PTO-1390 (Modified)
(REV 11-98)

U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

ATTORNEY'S DOCKET NUMBER

TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371

31919.3993

U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR 1.5)

09/786239

INTERNATIONAL APPLICATION NO.
PCT/US99/20297INTERNATIONAL FILING DATE
03 SEP 1999PRIORITY DATE CLAIMED
04 SEP 1998

TITLE OF INVENTION

FOOTWEAR SOLE AND ARCH STRAPPING SYSTEM

APPLICANT(S) FOR DO/EO/US

Brett D. RITTER; Damon R. BUTLER, Barry Joseph McGEOUGH; Edward J. NORTON; Zenon O. SMOTRYCZ

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☐ This is an express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).
4. ☒ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371 (c) (2))
 - a. ☐ is transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ has been transmitted by the International Bureau.
 - c. ☒ is not required, as the application was filed in the United States Receiving Office (RO/US)
6. ☐ A translation of the International Application into English (35 U.S.C. 371(c)(2)).
7. ☒ A copy of the International Search Report (PCT/ISA/210).
8. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371 (c)(3))
 - a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ have been transmitted by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☒ have not been made and will not be made.
9. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
10. ☒ An oath or declaration of the inventor(s) (35 U.S.C. 371 (c)(4)). (unsigned)
11. ☒ A copy of the International Preliminary Examination Report (PCT/IPEA/409).
12. ☐ A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371 (c)(5))

Items 13 to 20 below concern document(s) or information included:

13. ☐ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
14. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
15. ☐ A **FIRST** preliminary amendment.
16. ☐ A **SECOND** or **SUBSEQUENT** preliminary amendment.
17. ☐ A substitute specification.
18. ☐ A change of power of attorney and/or address letter.
19. ☐ Certificate of Mailing by Express Mail
20. ☒ Other items or information:

Statement Claiming Small Entity Status (37 CFR 1.9(f) & 1.27(c)) - Small Business Concern

Reply to Written Opinion which amended Claims 1-6 (and cancelled Claims 7-15) under Article 34.
(The favorable IPER is based on amended Claims 1-6.)

**VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY
STATUS (37 CFR 1.9(f) AND 1.27 (c)) - SMALL BUSINESS CONCERN**

Docket No.
31919.3993

Serial No.

Filing Date
Feb. 27, 2001

Patent No.

Issue Date

Applicant/ **Mark THATCHER**
Patentee:

Invention: **FOOTWEAR SOLE AND ARCH STRAPPING SYSTEM**

I hereby declare that I am:

- ☒ the owner of the small business concern identified below:
☐ an official of the small business concern empowered to act on behalf of the concern identified below:

NAME OF CONCERN: **Mark Thatcher**

ADDRESS OF CONCERN: **1245 Cochran Avenue, Flagstaff, Arizona 86001 US**

I hereby declare that the above-identified small business concern qualifies as a small business concern as defined in 13 CFR 121.3-18, and reproduced in 37 CFR 1.9(d), for purposes of paying reduced fees under Section 41(a) and (b) of Title 35, United States Code, in that the number of employees of the concern, including those of its affiliates, does not exceed 500 persons. For purposes of this statement, (1) the number of employees of the business concern is the average over the previous fiscal year of the concern of the persons employed on a full-time, part-time or temporary basis during each of the pay periods of the fiscal year, and (2) concerns are affiliates of each other when either, directly or indirectly, one concern controls or has the power to control the other, or a third party or parties controls or has the power to control both.

I hereby declare that rights under contract or law have been conveyed to and remain with the small business concern identified above with regard to the above identified invention described in:

- ☐ the specification filed herewith with title as listed above.
☒ the application identified above.
☐ the patent identified above.

If the rights held by the above-identified small business concern are not exclusive, each individual, concern or organization having rights to the invention is listed on the next page and no rights to the invention are held by any person, other than the inventor, who could not qualify as an independent inventor under 37 CFR 1.9(c) or by any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e).

Each person, concern or organization to which I have assigned, granted, conveyed, or licensed or am under an obligation under contract or law to assign, grant, convey, or license any rights in the invention is listed below:

- ☒ no such person, concern or organization exists.
☐ each such person, concern or organization is listed below.

FULL NAME

ADDRESS

☐

Individual

☐

Small Business Concern

☐

Nonprofit Organization

FULL NAME

ADDRESS

☐

Individual

☐

Small Business Concern

☐

Nonprofit Organization

FULL NAME

ADDRESS

☐

Individual

☐

Small Business Concern

☐

Nonprofit Organization

FULL NAME

ADDRESS

☐

Individual

☐

Small Business Concern

☐

Nonprofit Organization

Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities. (37 CFR 1.27)

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

NAME OF PERSON SIGNING:

Mark Thatcher

TITLE OF PERSON SIGNING

OTHER THAN OWNER:

Owner

ADDRESS OF PERSON SIGNING:

1245 Cochran AvenueFlagstaff, Arizona 86001US

SIGNATURE:



DATE:

2/26/08

FOOTWEAR SOLE AND ARCH STRAPPING SYSTEM

09/786239

BACKGROUND1. Field of the Invention

The present invention relates to footwear. In particular, the present invention is related to strapping systems for securely affixing footwear to a user's foot, and to shanks for providing rigidity and support to shoe soles.

2. Background of the Invention

There is a wide variety of prior art showing strapping configurations for footwear. Generally, the purpose of such strapping may be summarized as securing the footwear to a user's foot and is often used in connection with sandals.

Examples of prior art showing sandal or footwear strapping arrangements include U.S. Patents Nos. 4,200,997 and 4,446,633 to Scheinhaus, U.S. Pat. No. 4,679,334 to McBride, U.S. Pat. No. 3,327,410 to Park, U.S. Pat. No. 4,793,075 to Thatcher, U.S. Patent No. 4,817,302 to Saltsman, U.S. Patent No. 4,300,294 Riecken, U.S. Patent No. 2,788,591 to Gibson, U.S. Patent No. 2,126,094 to Daniels, and U.S. Patent No. 2,862,311 to Ellis. Each of these patents disclose strapping configurations which generally engage the ankle, heel, instep, toes, arch, or some combination thereof to secure the footwear to the user's foot. None of these prior art disclosures, however, nor any other existing strapping configurations have been entirely satisfactory in securing footwear to the foot while maintaining a comfortable, durable, and convenient configuration. This problem is particularly acute for sandals used in sports or other vigorous activities. As sandals have become more frequently worn in these active endeavors, demands on strapping configurations have grown. No known existing sandal strapping configuration allows for the natural adjustments of the foot and ankle during activity; such adjustments would enhance user comfort and ease of use.

One particular problem relates to ankle or instep straps. As the angle between the foot and the ankle changes during normal walking or running, the foot's main tendon that travels down the front of the leg and across the instep of the foot is alternately tightened and loosened. This causes the overall circumference of the ankle and instep to increase and decrease. Any strapping that wraps the ankle must allow

for this expansion and contraction, which necessitates such strapping to be able to compensate for the size variation. Without such compensation, the ankle strapping may overly restrict foot movement.

Prior footwear straps are typically oriented in a direction that does not correspond to the force vectors that occur during walking, running, or vigorous activity. Strapping usually is oriented at an angle of approximately 90° from the sole. This angle is appropriate to maximize strapping strength only when the strap lies flat and parallel to the sole on the foot surface. As the top of the foot slopes forward, however, a strap oriented at a 90° angle from the sole must twist to lie flat on the sloping foot surface. This causes discomfort in the user and diminishes the strength capacity of the strap.

Still other prior art footwear strapping configurations feature a continuous strap that contacts the wearer's foot in multiple locations, such as around the ankle, across the instep, and over the front of the foot. Such straps cannot remain taut during activity, due to movement of other portions of the foot. A continuous strap that covers both the instep and the forefoot, for instance, may lack the continuous, taut fit over the instep due to movement of the forefoot.

In addition to footwear strapping systems, other problems related to movement of the sole in relation to the foot also remain unresolved by the prior art. In particular, difficulties are associated with providing torsional rigidity, arch support, and overall stiffness to a sole during walking, running, or other vigorous activity. While a generally soft and cushioned sole forefoot and heel portion are desirable for wearer comfort, they may result in a sole being undesirably soft and "floppy". To prevent this condition, a relatively stiff and rigid shank may be provided to bridge the softer, less rigid forefoot and heel portions. The more rigid shank also provides torsional rigidity to the sole, preventing undesirable twisting motions during a wearer's stride.

Prior art shanks include metal plates inserted in the midfoot region between the midsole and either an outsole or an insole; a laterally narrow section of rubber or other material attached to the bottom outsole in the midfoot region (generally known as a "fiddleshank"); and other plastic components molded or glued to the sole midfoot region for support and rigidity. Such prior art shanks do not, however, adequately prevent and generally, are not well-configured to counteract the twisting type of

torsional forces developed during wearing of footwear, especially those forces caused by straps that pass through the sole.

Numerous unresolved needs therefore exist relating to footwear. A long felt need exists for a footwear strapping configuration that accommodates the foot's wide
5 range of movement during sports or other vigorous activities. In addition, a need exists for strapping that is capable of dynamically adjusting itself as required during such use. Further, unresolved needs exist for an integral, stiff and rigid shank portion to provide torsional rigidity and stiffness to an otherwise relatively soft and cushioned footwear forefoot and heel portions.

10

SUMMARY OF THE INVENTION

A first embodiment of the present invention comprises a unique strapping configuration for footwear that provides for dynamic fit adjustment while securely and comfortably affixing a sole to a wearer's foot. The strapping generally includes an adjustable X configuration strap which is attached in some manner to a heel portion
15 of the footwear, crosses over the wearer's instep, and passes through a transverse channel in the midsole of the footwear under the wearer's arch. The present invention further comprises footwear incorporating the unique strapping configuration that securely fastens the footwear to the user's foot, even during sports or other vigorous activities.

20

The adjustable X configuration instep strap generally has a first end secured to a first side of a heel portion of the footwear, crosses forwardly and transversely over the wearer's instep, passes through a channel in the sole of the footwear at the midfoot, the longitudinal center of the sole, extends rearwardly and transversely back across the
25 wearer's instep (thereby forming an X over the instep), and is adjustably and releasably secured to the second side of the heel portion of the footwear. The channel may be angled downwardly from rear to front in the longitudinal direction, parallel to the downward slope of the wearer's instep, so that the strap will lie flat on the wearer's instep and thereby more evenly carry forces that develop between the foot and the sole during sports or other vigorous activities.

30

The X configuration instep strap acts to secure the wearer's foot to the footwear sole. The strap preferably passes under the wearer's arch through the midfoot

channel, and thereby works to secure the transverse midfoot portion of the sole to the bottom of the wearer's foot.

The portion of the footwear sole through which the midfoot channel passes, the midfoot shank, is preferably comprised of a relatively stiff and hard material.

- 5 Incorporation of such shank material enables the channel to not significantly compress and thereby not pinch the strap passing through it during use. The strap may thus be free to move through this channel as the foot moves in different directions during use. The sole including the arch channel may be manufactured separate from the sole and may be affixed thereto by molding or with an adhesive. This allows for the shank
- 10 including the midfoot channel to be constructed of a relatively hard and stiff material and to be conveniently attached to a softer, more pliable sole. Alternatively, the shank portion may also be an integral portion of the sole. The relatively stiff and resilient arch channel also functions as a standard type shank to add desirable stiffness and torsional rigidity to the sole, as will be discussed in greater detail below in relation to
- 15 additional embodiments of the invention.

- In addition to the X-strap of the invention, the preferred sandal embodiment further may comprise a front strap system for releasably attaching the sole to the forefoot, and a heel strap system for releasably attaching the sole to the wearer's heel. Preferably, the heel strap system may include a pair of opposing heel posts that may
- 20 extend upward from the sole at the medial and lateral sides of the heel portion of the sole. Further, the heel strap system may include a T-strap having a downwardly extending portion that attaches to the center, rear of the sole, behind the wearer's Achilles tendon. The two free ends of the X-strap can be connected to the front of the lateral and medial heel posts. A side member or lateral strap may be further used that
- 25 extends from the lateral heel post to the front strap to provide additional support for the foot. However, additional strap configurations now known or hereafter devised by those skilled in the art may be utilized.

- As indicated above, the present invention optionally further comprises a footwear sole having relatively soft, low density forefoot and heel portions with a
- 30 higher density, more rigid shank portion. The two distinct density materials may be hot compression molded together to form a structurally integral unit. The high density, more rigid shank portion of the invention may, but need not, comprise the

transverse channel described above for passing a strap. In addition, the sole of the invention may be particularly well suited for, but is not limited to, use in sandals.

In accordance with various aspects of the present invention, the sole may comprise a molded unit of two or more different densities of thermoplastic or thermosetting polymer compounds. One compound may be of suitably low density and hardness to provide flexibility and cushion. Near the midfoot region of the sole, underlying the user's arch, is a shank portion comprising a denser, harder, stiffer compound. The presence of the higher density, stiffer shank tends to insure that the arch of the foot will have improved support. In addition, the relatively stiff shank is desirable to lend structure and support to the sole at the midfoot region where the outsole does not touch the ground, to provide a desirable overall stiffness to the sole during walking, and to provide torsional rigidity. The structural effect of the shank may be easily controlled by varying the hardness of the shank as desired.

Before explaining the several embodiments of the disclosure in detail, it is to be understood that the disclosure is not limited in its application to the details of the construction and the arrangements set forth in the following description or illustrated in the drawings. The present invention is capable of other embodiments and of being practiced and carried out in various ways, as will be appreciated by those skilled in the art. Also, it is to be understood that the phraseology and terminology employed herein are for description and not limitation.

The advantages of the present invention will become more fully apparent from the following detailed description when read in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWING FIGURES

FIG. 1 is a perspective view of one embodiment of a strapping system of the present invention;

FIG. 2 is a detail of one embodiment of a fastener for use in connection with of the strapping system of the present invention;

FIG. 3 is a detailed medial side view of the midfoot channel useful in connection with the strapping system of the present invention;

FIG. 4 is a bottom plan view of the midfoot channel of the strapping system of the present invention;

FIG. 5 is a perspective view of one embodiment of a footwear article of the present invention incorporating the strapping system of the present invention;

5 FIG. 6 is a plan view of one embodiment of a sole of the present invention having an integral shank;

FIG. 7 is a cross section taken along the line 7-7 of Fig. 6;

FIG. 8 shows a bottom and medial side perspective view of a second embodiment of a midsole of the present invention having an integral shank; and,

10 FIG. 9 is an exploded top and medial side perspective view of the second embodiment of a midsole of the present invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS **OF THE INVENTION**

Turning now to the drawing figures, Fig. 1 is a perspective view of footwear showing one embodiment of the strapping system of the present invention. The footwear may be of any type, including sandals. The footwear, as is conventional, includes a forefoot and heel portions, with a midfoot portion therebetween. In accordance with certain aspects of the present invention, a channel 31 is provided through the midfoot portion of a sole of the footwear, underlying the user's arch, as more fully explained below.

20 Preferably, strap 1 is operatively attached at a first end 3 to one side, e.g. the lateral side, of the heel portion of the footwear. Strap 1 preferably extends transversely across and forwardly across and over the instep of a wearer's foot. In accordance with certain aspects of the present invention, a strap passes through
25 midfoot channel 31, entering at a medial side 5 and emerging at a lateral side 9. Strap 1 then preferably extends in a rearward, transverse direction back across the foot instep. Strap 1 is preferably adjustably attached at a second end 11 to the medial side of a heel portion of the footwear.

While the heel strap system (heel portion) 12 is generally shown in Fig. 1 as comprising two upstanding posts 14, 15 and a heel strap 16 interconnected
30 therebetween, it should be appreciated, as previously briefly noted, that other strap

configurations or heel portions may be used. For example, the heel strap system may comprise a unitary structure formed of webbing or other material, or may comprise a plurality of interconnected straps. These and other modifications are within the scope of the present invention.

5 Moreover, it should be appreciated that ends 3 and 11 may be attached to heel portion 12 at any desirable location, for example at any point along the path traversed by strap 16.

One attachment device useful for attaching at least a portion of strap 1 to heel portion 12 is illustrated in Fig. 2, comprising mating hook and loop fasteners. In
10 accordance with this embodiment, strap 1 passes through a pivot loop 21 attached to the heel post 15 of the footwear. A section of mating hooks 23 are preferably located on the bottom of strap 1 near strap second end 11. A corresponding section of mating loops 25 are located on the top side of strap 1. Strap 1 may thereby be adjustably and removably attached to itself by pulling it through pivot loop 21 to a desired tightness
15 and releasably fixing section of hooks 23 onto section of loops 25. Other attaching devices may comprise mating female - male connectors, buckles, friction buckles, snaps, buttons, shoe laces, or other fasteners now known or hereafter devised in the art. Moreover, strap 1 may be adjustably attached at end 3 to heel portion 12, or alternatively not be adjustably attached to either end 11 or 3.

20 Preferably, strap 1, as previously noted, passes through channel 31. In accordance with various alternative embodiments, however, strap 1 may be attached to or within the sole 8.

With reference now to Fig. 4, channel 31 preferably extends across the width of the midfoot region of the sole and is substantially perpendicular to a longitudinal axis
25 of the sole. Angular orientations, for example, from front to back or vice versa, may also be utilized.

In accordance with various aspects of the present invention sole midfoot region 7 may include a shank 7. Shank 7 may comprise any resilient, stiff material to help prevent channel 31 from collapsing and pinch strap 1 when force is applied downward
30 on the shank 7 during use. The stiffness and resiliency of shank 7 also tends to impart advantageous strength and torsional rigidity to the sole. Shank 7 may be manufactured separate from the softer and more pliable sole and attached thereto with

an adhesive or the like. Alternative methods of manufacture may be used, such as molding the shank integrally with the other portions of the sole as will be described below. In cases where shank 7 comprises a separate component, channel 31 may be molded directly into shank 7, or a passageway, groove or other device may be formed on shank 7 to permit passage of strap 1 therewithin or therewithon.

In accordance with a preferred aspect of the present invention, strap 1 is free to move through channel 31, thereby tending to enable a dynamic, self adjusting fit. For example, as the foot may shift and move about during use, midfoot channel 31 allows strap 1 freedom to respond. This allows for strap 1 to maintain its fit across the foot instep and for maintenance of a correspondingly firm, responsive, and comfortable fit even during vigorous activity. However, movement of strap 1 in channel 31 is not required.

With reference now to Fig. 3 an expanded medial side view of channel 31 in the sole midfoot region 7 shows strap 1 passing there through. Midfoot channel 31 may be generally configured in any desirable orientation. Preferably, and with continued reference to Fig. 3, channel 31 is angled forward and downward at an angle of \emptyset . Angle \emptyset is preferably between about 2° and about 15° , and more preferably between about 3° and about 6° measured from a horizontal plane as shown in Fig. 3. In accordance with this aspect, as the respective ends of the X-strap 1 extend upward and over the wearer's instep, the angle \emptyset will tend to be maintained, thus causing the surface of strap 1 to lie approximately flat on the sloping instep of the wearer's foot. Angling the channel in a downward and forward longitudinal direction tends to desirably direct the respective ends of strap 1 in a forward and upward direction closely matching a typical forward and upward direction that the sole is pulled by the foot during walking or running. In this manner the angling of channel 31 may maximize the ability of strap 1 to absorb forces developed during use, and provides for user comfort as strap 1 will tend to lie flat on a wearer's instep. However, other midfoot channel configurations with channel 31 extending horizontally, upwardly or other configurations may be employed.

Strap 1 may be fabricated from any suitable flexible material having sufficient tensile strength, such as a woven fabric, leather, suede, and any known material in the art. A preferred strap comprises woven nylon as is well known in the art. Fabric

weaves may optionally comprise reflective material, thereby providing 360° reflectivity for enhanced user safety.

While the strap assembly set forth in Fig. 1 and variously referred to herein as a “strap assembly” may be used on a variety of footwear products, a preferred embodiment in accordance with the present invention comprises a sandal 40, such as is shown in Fig. 5. Sandal 40 preferably includes a sole 51 and a variety of straps including a version of the strap assembly hereof connected thereto. Preferably, a strap 41 has a first end 43 attached to a heel post 45. Strap 41 passes over a foot instep and into a channel 47. Channel 47 preferably extends transversely through sole 51. After exiting channel 47, strap 41 passes back over the foot instep, through a midfoot loop 53. A fastener 55 for adjustable fastening of strap 41 to heel post 57 cooperates to secure strap 41 to loop 53. Strap 41 thereby forms an X-shape over the wearer’s instep. Fastener 55 may comprise a buckle with lever as illustrated, or other means as are known in the art, including, for example, hook and loop fasteners, male-female connectors, buckles, buttons, snaps, shoe laces, and the like.

Sole midfoot region 49 may be fabricated from a resilient and relatively stiff material to provide desirable torsional rigidity to the softer and more pliable sole 51. In addition, the stiff and relatively rigid construction of midfoot region, or shank 49, provides support to the arch region of a wearer’s foot. Advantages related to torsional rigidity and arch region support will be discussed in greater detail below in association with additional embodiments of the invention.

Because preferred sole midfoot region 49 may be comprised of a resilient plastic material while sole 51 may be comprised of a softer, more pliable material, sole midfoot region 49 is preferably manufactured separate from sole 51 and then affixed thereto using adhesives or the like. Midfoot region 49 need not necessarily be prepared separately from sole 51 and attached thereto; it may also be integral with sole 51. Sole 51 is constructed as generally known in the art, and may, for example, be comprised of a relatively tough and wear resistant outsole, and a softer and more cushioned midsole. A soft insole or footbed for contact with the wearer’s foot may be adhered to the upper surface of the sole. As used herein, the term “sole” refers to the structural sole of the footwear, and includes a unitary sole, an outsole and/or midsole,

but does not encompass an insole. Sole 51 is preferably molded of ethylene vinyl acetate.

5 A heel strap 59, for securing a wearer's heel to the footwear, is preferably attached at a first end 61 to a medial heel post 45, and at a second end to lateral heel post 57. Heel strap 59 second end 63 preferably is adjustable, and thus may extend through heel loop 65, and through a heel fastener 67. Fastener 67 may comprise any of several fasteners that are well known in the art, including, for example, a lever operated buckle as illustrated, mating hooks and loops, mating male/female buckles, buttons, laces, snaps, or the like. Heel strap 59 desirably may be provided with a
10 downwardly extending T-strap member (not shown) that attaches to the center, rear of the sole. If a T-strap is utilized, heel strap fasteners may be provided at one or both of the lateral and medial heel posts so that the wearer may adjust the T-strap as desired. As previously noted, other heel strap configurations may also be used.

Sandal 40 may also include a lateral side member 59 and forefoot strap 69.
15 Lateral side member 59, when employed, preferably extends between heel post 57 and forefoot strap 69. Forefoot strap 69 adjustably secures a wearer's forefoot to sole 51. For example, forefoot strap 69 may be adjustably tightened through front loop 71, and fastened back onto itself through fastener 73. Fastener 73 may comprise any of the several fasteners as known in the art, including, for example, mating hook and loop
20 fasteners, buttons, laces, buckles, and the like.

Although various of the embodiments of the invention have been illustrated and described herein as generally in use with sandals, it will be understood by those knowledgeable in the art that the X-strap of the invention may likewise prove advantageous for use with other types of footwear. In particular, the X-strap of the
25 invention will be useful in any application where a snug, responsive, and dynamic fit between foot and footwear is desired.

As discussed above, the present invention may optionally further comprise an improved shank configuration for providing a footwear sole with torsional rigidity, arch support, and stiffness. These advantages are best described in relation to the
30 invention embodiments illustrated in Figs. 6-9.

Fig. 6 is a plan view of an embodiment of a sole 110 comprising a sole piece 112 and an integral shank 114 fused therein. Sole piece 112 is generally in the shape

of a foot and includes a forefoot portion 116, a heel portion 118, a medial side 120 and a lateral side 121. Sole piece 112 may be comprised of a wide variety of thermoplastic and thermosetting polymer compounds. Ethylene vinyl acetate ("EVA") foam is preferred, but other compounds may be used. The density and hardness of sole piece 112 may be set as desired, with a relatively soft, cushioned consistency desirable for foot comfort. Hardness ranges for sole piece 112 will range between about 30 and about 60 Shore C hardness, with a preferred hardness of about 55 +/- 2 Shore C. Shank 114 resides in the midfoot region of sole 110, underlying the user's arch and bridging the heel and forefoot region.

Shank 114 preferably extends all the way through the sole 110 in a vertical direction, as best seen in Fig. 7. In addition, shank 114 is not located only in either the medial or lateral portion of sole 110, but preferably extends into both portions for optimum torsional rigidity. An embodiment of the shank of the invention may extend substantially across the transverse width of the footwear sole, as generally described hereinabove with reference to previous footwear embodiments of the invention. The specific configuration of the shank is not critical, but preferably Shank 114 is sized to bridge between the heel and forefoot regions of the sole. Shank 114 may also be comprised of a suitable thermoplastic or thermosetting polymer compound, with EVA foam preferred. Shank 114 may optionally comprise a channel (like channel 31 shown in Fig. 1) for passing a strap as described above with reference to previously illustrated embodiments of the invention. The composition of shank 114 is denser, and hence stiffer and harder, than sole piece 112. In accordance with certain embodiments of the present invention, shank 114 preferably has a hardness in the range of between about 55 and about 85 Shore C hardness, with a preferred hardness of about 80 +/- 2 Shore C. Preferably a differential of about 20 to about 30 Shore C hardness exists between sole piece 112 and shank 114.

A preferred method of making the integral sole piece 112 and shank 114 of the invention comprises the steps of cutting out a portion of sole piece 112 corresponding to the shape of shank 114, cutting out a shank piece 114 from suitable hardness material, and hot compression molding shank 114 into sole piece 112. Chemical cross-linking bonds are thereby formed between shank 114 and sole piece 112,

integrally fusing shank 114 with sole piece 112. Other methods of attachment comprise use of adhesives or the like.

5 Figs. 8 and 9 illustrate a sole in accordance with an additional embodiment of the invention. Fig. 8 is a bottom and medial side view of a midsole of the invention, while Fig. 9 is an exploded top and medial side view of the entire sole of this embodiment. Midsole piece 150 preferably has a bottom surface 151 and an integrally molded midfoot shank 152. Shank 152 is preferably comprised of EVA foam with a hardness of between about 55 and about 85 Shore C, while midsole piece 150 is preferably comprised of EVA foam with a hardness of between about 30 and
10 about 60 Shore C, approximately 20-30 Shore C less than shank 152.

Midsole piece 150 is preferably configured to include an upwardly arched midfoot portion 154 that extends laterally across the sole. The medial side of midfoot 154 preferably has a thicker, raised portion 156 adapted to underlie and support the user's medial arch. In this embodiment, the bottom surface of shank 152 is preferably
15 molded to provide two opposing lobes 162 protruding downwardly at the lateral and medial midfoot, and thereby forming a shallow groove 164 between them. The foregoing features, including the arch 154, raised portion 156, lobes 162 and groove 164, are preferably formed when the midsole sole piece 150 and shank 152 are hot compression molded together to form integral midsole 170.

20 A shock pad 153 is optionally provided, preferably at the center of the heel region 155. Pad 153 may be separately formed and may be inserted into a molded cavity in midsole 150 to absorb energy from a heel strike and release the energy when the user moves forward in a resilient, spring-like manner. Shock pad 153 operates in combination with shank 152 to reflect and rebound energy in a forward direction.
25 This combination has been found to provide benefits over either shock pads or integral shanks employed individually.

Turning now to Fig. 9, midsole 170 is preferably sandwiched between a top sole 172 and an outsole 174. A top surface 176 of shank 152 preferably having a raised arcuate portion 178 protrudes upwardly on the medial side of the midfoot, underlying
30 the user's medial arch. Integral midsole 170 has a raised perimeter edge 180 and a broad recessed area 182 between edge 180 and the raised arcuate portion 178. Top sole 172 is affixed to the top surface of integral sole 170 as depicted in Fig. 7. An

exemplary embodiment of top sole 172 has a shape and thickness that correspond to the recess 182 in the midsole 170, so that a substantially flush surface results upon attachment of the top sole to the midsole. Top sole 172 is preferably comprised of EVA foam with a hardness of about 20 to about 40 Shore C durometer.

5 Top sole 172 may have an arcuate indentation 184 at the medial midfoot to match raised portion 178 of shank 152 thereby enabling exposure of portion 178 when top sole 172 is in place. Alternatively, top sole 172 may completely cover shank 152 including raised portion 178. In either case, however, preferably a substantially flush outer surface is obtained. For example, outsole 174 may include a raised ridge 186
10 about its outer perimeter that will wrap around outer, lower edges 187 of the midsole. A preferred outsole raised edge 186 has opposing front side portions 188, opposing rear side portions 190, front end 192, and back end 194 that are raised higher than the remainder of raised edge 186. These regions correspond to areas of increased wear, thereby making durable outsole 174 desirable.

15 Outsole 174 preferably includes a bridge portion 196 which rests in the shank groove 164 of the midsole. Placement of bridge portion 196 in groove 164 helps to stabilize outsole 174 from lateral movement relative to the midsole. Outsole 174 may be comprised of any resilient, rubber like material, or polyurethane, and is preferably attached to the bottom of integral sole 170.

20 The advantages of the disclosed invention are thus attained in an economical, practical, and facile manner. While preferred embodiments and example configurations have been shown and described, it is to be understood that various further modifications and additional configurations will be apparent to those skilled in the art. It is intended that the specific embodiments and configurations herein
25 disclosed are illustrative of the preferred and best modes for practicing the invention, and should not be interpreted as limitations on the scope of the invention as defined by the appended claims.

CLAIMS

What is claimed is:

- 1 1. An X-strap assembly for securing an article of footwear to the instep of a
2 foot, said footwear having a sole and channel through said sole, said strap assembly
3 comprising:
4 a) a strap attached at its respective ends to medial and lateral heel
5 sides of said footwear, said strap having a first portion extending in a forward
6 direction transversely across the instep from a first side of said footwear to a second
7 side, a second portion extending through said channel, and a third portion extending in
8 a rearward direction transversely across the instep from said instep from said second
9 side to said first side of said footwear, said first and said third portions forming an X-
10 configuration over said instep; and
11 b) a fastener attached to said strap.
- 1 2. An article of footwear, comprising:
2 a) a sole, the sole having a midfoot portion and a heel portion;
3 b) a channel extending transversely across the midfoot portion of said
4 sole and at least partly under said sole;
5 c) an instep strap connected to said heel portion of said sole, said strap
6 having a first portion extending in a forward direction transversely across a wearer's
7 instep from one side of said sole to the other, a second portion extending through said
8 channel and slidable within said channel, and a third portion extending in a rearward
9 direction transversely across the wearer's instep from said other side to said one side
10 of said sole, the first and third portions of said strap forming an X configuration over
11 the wearer's instep, and the second portion being between the first and third portions
12 of said strap; and
13 d) an adjustable fastener attached to said strap for adjusting said
14 strap.
3. An article of footwear as in claim 2, wherein said midfoot portion of said sole includes a shank, said shank at least partly underlying said sole, said shank being stiffer than said sole, said channel extending through said shank.

1 4. An article of footwear, as in claim 3, wherein said channel is angled
2 downwardly from rear to front in a longitudinal direction;

1 5. An article of footwear as in claim 4 further comprising a heel portion strap
2 assembly, a forefoot strap assembly and a lateral strap extending therebetween.

1 6. A footwear product to be worn by a user on the user's foot, comprising:
2 a) a sole;
3 b) a transverse passageway extending through said sole; and
4 c) a strap system configured to secure the footwear product to the user's
5 foot including:
6 a heel portion,
7 an X-strap assembly coupled to said heel portion, wherein said X-strap
8 assembly includes a continuous strap having a first portion extending transversely
9 across the user's instep from a first side of the footwear to a second side, a second
10 portion extending through said transverse passageway, and a third portion extending
11 transversely across the user's instep from said second side to said first side of said
12 footwear, said first and said third portions of said X-strap assembly forming an
13 X-configuration over the user's instep, and
14 an adjustable fastener for adjusting the length of said X-strap assembly.

1 7. A sole having a forefoot, heel, and midfoot therebetween, comprising:
2 a) a foot shaped sole piece of a polymer compound of selected hardness;
3 and
4 b) a shank within the midfoot of said sole piece and bridging between
5 the forefoot and heel, said shank having a higher hardness than said sole piece, and
6 said shank being integrally fused to said sole piece.

8. A sole as in claim 7, wherein said sole is a sandal sole.

9. A sole as in claim 7, wherein said shank has a bottom surface with a longitudinal groove, and said outsole has a longitudinal bridge portion seated within said groove.

10. A sole as in claim 7, further comprising a traverse channel extending through said shank.

11. A sole as in claim 7, wherein said shank has a hardness of about 20 to 30 Shore C greater than said sole piece.

12. A sole as in claim 11, wherein said sole piece and said shank are molded from different color compounds.

13. A sole as in claim 12, wherein said shank has a channel therethrough for movably passing a strap.

14. An article of footwear comprising:
a) a foot shaped sole piece having a medial and a lateral side; and
b) a shank integrally molded in said sole piece, said shank having a hardness greater than the hardness of said sole piece, said shank extending substantially from said sole lateral side to said sole medial side, said shank having a transverse channel adapted to movably pass a strap therethrough.

15. An article of footwear as in claim 14, further comprising an x-strap assembly at least a portion of which extends through said channel.

1/5




FIG. 2




FIG. 1




FIG.3




FIG.4



4/5




FIG. 6




FIG. 7




FIG. 8




FIG. 9

Applicant(s): RITTER, Brett D., et al.

Atty. Docket No.: 31919.3993

Serial No.: 09/786,293

Filing Date: 27 FEB 01

Group Art Unit: to be assigned

Examiner: to be assigned

TITLE: FOOTWEAR SOLE AND ARCH
STRAPPING SYSTEM

POWER OF ATTORNEY


Mark Thatcher, an individual residing at 1245 Cochran Avenue, Flagstaff, Arizona 86001 US, certifies that to the best of his knowledge and belief, he is the assignee of the entire right, title, and interest in and to the above-captioned United States patent application and represents that he is authorized and empowered to sign in his capacity as assignee.

Mark Thatcher, the Assignee of the entire right, title, and interest in and to the above-captioned United States patent application and all inventions disclosed and claimed therein, hereby appoints as his attorneys to prosecute the above-captioned United States patent application and to transact all business in the United States Patent and Trademark Office connected therewith and with the resulting patent, individually and collectively:

Deborah M. Chess, Esq.
SNELL & WILMER L.L.P.
One Arizona Center
400 East Van Buren
Phoenix, Arizona 85004-0001
Tel. (602) 382-6000
Fax (602) 382-6070

and the registered attorneys associated with Snell & Wilmer's Customer Number 020322.

Please send all further correspondence to Snell & Wilmer L.L.P. at the above address.


Mark Thatcher

Date: 5/6/01

Please type a plus sign (+) inside this box → ☐

PTO/SB/01 (12/97)
Approved for use through 9/30/00. OMB 0651-0032

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION (37 CFR 1.63) <input type="checkbox"/> Declaration Submitted with Initial Filing OR <input checked="" type="checkbox"/> Declaration Submitted after Initial Filing (surcharge (37 CFR 1.16(e)) required)	Attorney Docket Number	31919.3993
	First Named Inventor	Brett D. RITTER, et al.
	COMPLETE IF KNOWN	
	Application Number	09 / 786,239
	Filing Date	February 27, 2001
	Group Art Unit	To be assigned
	Examiner Name	To be assigned

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

FOOTWEAR SOLE AND ARCH STRAPPING SYSTEM

the specification of which (Title of the Invention)

☐ is attached hereto
OR
☒ was filed on (MM/DD/YYYY) 09/03/1999 as United States Application Number or PCT International

Application Number PCT/US99/20297 and was amended on (MM/DD/YYYY) 11/30/2000 (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above:

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?	
				YES	NO
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

☐ Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto:

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below.

Application Number(s)	Filing Date (MM/DD/YYYY)

☐ Additional provisional application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

[Page 1 of 2]

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Please type a plus sign (+) inside this box → ☐

PTO/SB/01 (12/97)
Approved for use through 9/30/00. OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION ---- Utility or Design Patent Application

I hereby claim the benefit under 35 U.S.C. 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. Parent Application or PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)
PCT/US99/20297	09/03/1999	

☐ Additional U.S. or PCT international application numbers are listed on a supplemental priority data sheet PTO/SB/103 attached hereto.

As a named inventor, I hereby appoint the following registered practitioner(s) to prosecute this application and to transact with the Patent and Trademark Office connected therewith: ☒ Customer Number 20322 OR ☐ Registered practitioner(s) name/registration number listed below

Name	Registration Number	Name	PATENT TRADEMARK OFFICE Number

☐ Additional registered practitioner(s) named on supplemental Registered Practitioner information sheet PTO/SB/02C attached hereto.

Direct all correspondence to: ☐ Customer Number or Bar Code Label 20322 OR ☒ Correspondence address below

Name	Deborah M. Chess				
Address	Snell & Wilmer, LLP				
Address	One Arizona Center, 400 East Van Buren				
City	Phoenix	State	AZ	ZIP	85004-2202
Country	US	Telephone	602-382-6388	Fax	602-382-6070

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name of Sole or First Inventor: Brett D. Ritter ☐ A petition has been filed for this unsigned inventor

Given Name (first and middle [if any])	Family Name or Surname
<u>Brett D.</u>	<u>RITTER</u>

Inventor's Signature					Date	3/7/01	
Residence: City	<u>Santa Barbara</u>	State	CA	Country	US	Citizenship	USA
Post Office Address	<u>3737 Torino Drive</u> <u>CA</u>						
Post Office Address							
City	<u>S.Barbara</u>	State	CA	ZIP	93105	Country	US

☒ Additional inventors are being named on the 2 supplemental Additional Inventor(s) sheet(s) PTO/SB/02A attached

Please type a plus sign (+) inside this box → ☐

PTO/SB/02A (12/97)

Approved for use through 9/30/98. OMB 0651-0032

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION

ADDITIONAL INVENTOR(S)
Supplemental Sheet

Page 1 of 2

Name of Additional Joint Inventor, if any:

☐ A petition has been filed for this unsigned inventor

Given Name (first and middle (if any))

Family Name or Surname

Damon R.

BUTLER

Inventor's
Signature*Damon R. Butler*

Date

3-8-01

Residence: City

Portland

State

OR

Country

US

Citizenship

UK.

Post Office Address

~~2024 N.E. 50th Avenue~~ 3228 NE 60TH AVE OR

Post Office Address

City

Portland

State

OR

ZIP

97213

Country

US

Name of Additional Joint Inventor, if any:

☐ A petition has been filed for this unsigned inventor

Given Name (first and middle (if any))

Family Name or Surname

Barry Joseph

McGEOUGH

Inventor's
Signature

Date

Residence: City

Santa Barbara

State

CA

Country

US

Citizenship

Post Office Address

1793 Calle Poniente

Post Office Address

City

Santa Barbara

State

CA

ZIP

93101

Country

US

Name of Additional Joint Inventor, if any:

☐ A petition has been filed for this unsigned inventor

Given Name (first and middle (if any))

Family Name or Surname

Edward J.

NORTON

Inventor's
Signature

Date

Residence: City

Boxford

State

MA

Country

US

Citizenship

Post Office Address

92 Middleton Road

Post Office Address

City

Boxford

State

MA

ZIP

01921

Country

US

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

0978669-0574

Please type a plus sign (+) inside this box → ☐

PTO/SB/02A (12/97)

Approved for use through 9/30/98. OMB 0651-0032

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number

DECLARATION**ADDITIONAL INVENTOR(S)****Supplemental Sheet**Page 1 of 2**Name of Additional Joint Inventor, if any:**☐ A petition has been filed for this unsigned inventor

Given Name (first and middle [if any])

Family Name or Surname

Damon R.**BUTLER**Inventor's
Signature

Date

Residence: City

Portland

State

OR

Country

US

Citizenship

Post Office Address

2024 N.E. 50th Avenue

Post Office Address

City

Portland

State

OR

ZIP

97213

Country

US**Name of Additional Joint Inventor, if any:**☐ A petition has been filed for this unsigned inventor

Given Name (first and middle [if any])

Family Name or Surname

Barry Joseph**McGEOUGH**Inventor's
Signature

Date

1-29-01

Residence: City

Santa Barbara

State

CA

Country

US

Citizenship

U.S.

Post Office Address

1793 Calle Poniente

Post Office Address

City

Santa Barbara

State

CA

ZIP

93101

Country

US**Name of Additional Joint Inventor, if any:**☐ A petition has been filed for this unsigned inventor

Given Name (first and middle [if any])

Family Name or Surname

Edward J.**NORTON**Inventor's
Signature

Date

Residence: City

Boxford

State

MA

Country

US

Citizenship

Post Office Address

92 Middleton Road

Post Office Address

City

Boxford

State

MA

ZIP

01921

Country

US

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

097863-0301

Please type a plus sign (+) inside this box → ☐

PTO/SB/02A (12/97)

Approved for use through 9/30/98. OMB 0651-0032

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION

ADDITIONAL INVENTOR(S) Supplemental Sheet

Page 1 of 2

Name of Additional Joint Inventor, if any:				<input type="checkbox"/> A petition has been filed for this unsigned inventor			
Given Name (first and middle [if any])				Family Name or Surname			
Damon R.				BUTLER			
Inventor's Signature					Date		
Residence: City	Santa Barbara	State	CA	Country	US	Citizenship	
Post Office Address		803 Moreno Road					
Post Office Address							
City	Santa Barbara	State	CA	ZIP	93103	Country	US
Name of Additional Joint Inventor, if any:				<input type="checkbox"/> A petition has been filed for this unsigned inventor			
Given Name (first and middle [if any])				Family Name or Surname			
Barry Joseph				McGEOUGH			
Inventor's Signature					Date		
Residence: City	Santa Barbara	State	CA	Country	US	Citizenship	
Post Office Address		1240 East Cota					
Post Office Address							
City	Santa Barbara	State	CA	ZIP	93103	Country	US
Name of Additional Joint Inventor, if any:				<input type="checkbox"/> A petition has been filed for this unsigned inventor			
Given Name (first and middle [if any])				Family Name or Surname			
Edward J.				NORTON			
Inventor's Signature		<i>Edward Jmh</i>			Date		3/19/01
Residence: City	Boxford	State	MA	Country	US	Citizenship	US
Post Office Address		92 Middleton Road MA					
Post Office Address							
City	Boxford	State	MA	ZIP	01921	Country	US

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Please type a plus sign (+) inside this box → ☐

PTO/SB/02A (12/97)
Approved for use through 9/30/98. OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION

ADDITIONAL INVENTOR(S)
Supplemental Sheet
Page 2 of 2

Name of Additional Joint Inventor, if any:				<input type="checkbox"/> A petition has been filed for this unsigned inventor			
Given Name (first and middle [if any])				Family Name or Surname			
<u>Zenon O.</u>				<u>SMOTRYCZ</u>			
Inventor's Signature	<u>Zenon O. Smotrycz</u>			3-15-01		Date	
Residence: City	<u>Reading</u>	State	<u>MA</u>	Country	<u>USA</u>	Citizenship	<u>USA</u>
Post Office Address	<u>51 Avalon Road MA</u>						
Post Office Address							
City	<u>Reading</u>	State	<u>MA</u>	ZIP	<u>01867</u>	Country	<u>US</u>
Name of Additional Joint Inventor, if any:				<input type="checkbox"/> A petition has been filed for this unsigned inventor			
Given Name (first and middle [if any])				Family Name or Surname			
Inventor's Signature						Date	
Residence: City		State		Country		Citizenship	
Post Office Address							
Post Office Address							
City		State		ZIP		Country	
Name of Additional Joint Inventor, if any:				<input type="checkbox"/> A petition has been filed for this unsigned inventor			
Given Name (first and middle [if any])				Family Name or Surname			
Inventor's Signature						Date	
Residence: City		State		Country		Citizenship	
Post Office Address							
Post Office Address							
City		State		ZIP		Country	

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.